

Synthetic Oven Chain Lubricant	Graphite Oven Chain Lubricant
Can be applied AUTOMATICALLY by an oiler system.	Can NOT be applied by an automatic oil applicator. Must be applied MANUALLY .
USDA Food Grade Approved – H1 or H2	NOT an USDA Food Grade Lubricant
Contains No Contaminating Odours, Carcinogens or Toxic Fumes hazardous to personnel and product.	Contains Toxic Chemicals, Odors, Carcinogens & Fumes hazardous to personnel and product.
NON-Hazardous Product - Shipping Class 65	Hazardous Product
Fire Resistant NON-Combustible Mixture Eliminate fear of fire and explosion!	Fire Hazardous - Combustible Mixture
Synthetic Lubricant stays 100% in Suspension. Mixing is Never required. No hard-packed sediments.	Graphite Lubricant SEPARATES from carrier. Mixing required at all times.
Reduces oven amperage load.	Requires frequent applications to reduce amperage load.
Provides maximum cleanliness. 100% Ash-less. No splatter or mess. Minimal build-Up. Requires minimal cleaning & maintenance.	Dirty Application. Splatters. Messy. Severe Build-up. Requires frequent cleaning & increased maintenance.
No build-up of sludge. Allowing the lubricant to FLOW into the chain.	Build-up of Sludge. Not allowing the lubricant to flow into the chain.
Synthetic Lubricant can be applied to either a HOT or COLD chain while in production. No drag on start-up.	Graphite Lubricant can NOT be applied while oven is hot. Must STOP production!
Virtually eliminates chain stretching.	100 year track record of chain stretching.